

**Technical leaflet Frigofilt filter drier with replaceable solid core, type HFF HP**

**Dimensions and weights for high -pressure version**

B	A	D	E	H	J	Weight
21,3	5/8" - 16 mm	22	175	228	93	3,30
26,9	7/8" - 22 mm	22	175	230	96	3,50
33,7	28 mm	22	175	233	90	3,55
42,4	1 3/8"-35 mm	22	175	235	102	3,65
48,3	42 mm	22	175	237	105	3,70
60,3	2 1/8"-54 mm	22	175	239	108	3,75
73	2 5/8"	22	175	242	115	3,90
26,9	7/8" - 22 mm	22	316	371	96	4,65
33,7	28 mm	22	316	374	99	4,80
42,4	1 3/8"-35 mm	22	316	376	102	4,90
48,3	42 mm	22	316	378	105	4,95
60,3	2 1/8"-54 mm	22	316	380	108	5,00
73	2 5/8"	22	316	383	115	5,15
89	3 1/8"	22	316	400	134	5,50
33,7	28 mm	22	459	517	99	6,15
42,4	1 3/8"-35 mm	22	459	519	102	6,20
48,3	42 mm	22	459	521	105	6,25
60,3	2 1/8"-54 mm	22	459	523	108	6,30
42,4	1 3/8"-35 mm	22	600	660	102	7,40
48,3	42 mm	22	600	662	105	7,45
60,3	2 1/8"-54 mm	22	600	664	108	7,50

A fedél és a karima vastagsága : 15 mm

