

**Technical leaflet Frigofilt filter drier with replaceable solid core, type HFF**

**Dimensions and weights for normal -pressure version**

B	A	D	E	H	J	Weight
21,3	5/8" - 16 mm	22	175	228	93	2,80
26,9	7/8" - 22 mm	22	175	230	96	2,90
33,7	1 1/8"	22	175	233	90	3,05
42,4	1 3/8"-35 mm	22	175	235	102	3,15
48,3	1 5/8"	22	175	237	105	3,20
60,3	2 1/8"-54 mm	22	175	239	108	3,25
73	2 5/8"	22	175	242	115	3,40
26,9	7/8" - 22 mm	22	316	371	96	4,15
33,7	1 1/8"	22	316	374	99	4,30
42,4	1 3/8"-35 mm	22	316	376	102	4,40
48,3	1 5/8"	22	316	378	105	4,45
60,3	2 1/8"-54 mm	22	316	380	108	4,50
73	2 5/8"	22	316	383	115	4,65
89	3 1/8"	22	316	400	134	5,00
33,7	1 1/8"	22	459	517	99	5,55
42,4	1 3/8"-35 mm	22	459	519	102	5,65
48,3	1 5/8"	22	459	521	105	5,70
60,3	2 1/8"-54 mm	22	459	523	108	5,75
42,4	1 3/8"-35 mm	22	600	660	102	6,90
48,3	1 5/8"	22	600	662	105	6,95
60,3	2 1/8"-54 mm	22	600	664	108	7,00

